# **In-vessel Calibration Light Source hardware status**

T.M. Biewer

Oak Ridge National Laboratory


Culham Science Centre, June 24, 2010



#### Oak Ridge National Laboratory

Managed by UT-Battelle for the Department of Energy

## In-vessel diagnostic calibration on JET




- ITER demonstration technology for in-situ, absolute intensity calibration of optical diagnostics via "remote handling."
- ~20 visible diagnostics to be calibrated on JET in 2010 using this technique.

OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY



# In-vessel Calibration Light Source(ICLS)



 Engineering Model as of June 7, 2010

3-connector design

4 lamps: 2x 100W, 2x 5W

Radiometer

- LED "torch"

Iris/shutter missing

Cameras not included


RH grip-mounts not shown

OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY




#### **ICLS** detail view

Engineering Model as of June 23, 2010



#### **ICLS** ex-vessel electronics



## ICLS ex-vessel electronics (cont.)

- Inputs to ex-vessel electronics: AC power and network cables
- Outputs
  - ICLS umbilical
  - Network to PC:
    - Labsphere control: lamps, shutter
    - AC power (on/off): cameras (2), LED "torch" (1), lamp power supplies (4), DVR box (1)
    - DVR data: camera signals (~5 day continuous recording capacity)
- PC can be located anywhere on JETnet

UT-BATTELLE

#### **Ancillary electronics tested**



- Mock-up of sphere with cameras, DVR, remote-AC, etc tested using ICLS PC
- Successful!
- PC, DVR, cameras, remote-AC, etc shipped to Labsphere (NH, USA)
- to be US/UK power and NTSC/PAL dual compatible


OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY

T.M. Biewer, ORNL

7/8

#### **Camera/DVR details**

- 2 B&W cameras
  - 600 TV lines (507x492 pixels)
  - 0.0003 lux sensitivity
  - auto-exposure




- DVR: simultaneous record, playback, transfer
  - 4-channel, 120 fps
  - 250GB capacity
  - ~5 days continuous recording (full resolution)
  - Web-viewable w/o loss of performance at 4 connections

OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY



## RH grip mounts in production





OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY

- "grip mounts"
   interface between RH
   MASCOT grippers and
   the ICLS sphere
- ORNL designed from JET "reference"
- Currently in production
  - Expected in "2 weeks"
  - To be shipped to Labsphere



#### JET production of hardware

- Transfer/storage "cradle" design waiting for Labsphere shutter drawings and final model
- RH connectors and socket box
  - LEMO shells and pins "in stock"
- Umbilical cable (3 cable bundle: 20m, 10m)
  - 2 of 3 LSZH cables are on-site with 20m sheathing
  - 1 cable and 10m sheathing in transit from US
  - RH technicians to fabricate ASAP
  - Ship to Labsphere



## Labsphere production of hardware

- Engineering drawings for shutter assembly
- Produce sphere shell, shutter, lamps, electronics, etc.
- Attach "usual" connectors to umbilical
- Attach socket box leads to ICLS components
- Interface with ancillary electronics (DVR, cameras, etc.)
- Calibration of lamp radiances
- Ship by August 1<sup>st</sup> directly to JET
  - T.B. visit to Labsphere to "accept" ICLS

OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY




#### Schedule and other

- Engineering drawings of the shutter and complete sphere
  - imminent
- Ensure JET hardware and cable headed towards Labsphere
  - June/July
- Production and testing of ICLS system
  - July
- Shipment to JET
  - "August 1st, 2010"
- RH testing and prep.
  - mid to end August
- ICLS use in JET
  - September




# Iris and cameras implementation: 1





# Iris and camera implementation: 2










U. S. DEPARTMENT OF ENERGY

UT-BATTELLE DOXPVIIduV


## RH compatible connectors



OAK RIDGE NATIONAL LABORATORY
U. S. DEPARTMENT OF ENERGY



#### Cable length verification



Estimated cable length from Oct outer limiter guide tube to top of outer vessel at Oct  $5 = \frac{15m}{2}$  However, some extra might need to be added to be safe. This does not include the length required ex-vessel to the power supply etc.

OAK RIDGE NATIONAL LABORATORY U. S. DEPARTMENT OF ENERGY

